

Standard Features:

- **Print, Fold and Seal:** One-step process eliminates excess document handling
- **Document Security:** Enclosed paper path from printer to pressure sealer ensures security. Ideal for PIN notices or other confidential applications
- **Form Capabilities:** Processes forms up to 14" in length
- **Printer Compatibility:** Designed to work with a variety of printers, including HP/Troy P2035, P4515, P3015, M451, M601, M602, M604, M605, M606, Lexmark MS700dn, and Xerox Phaser 4510. See specifications for additional printers.
- **Installation:** Easy to install, no software required
- **Alignment Base:** Special alignment base holds the printer and pressure sealer securely and slides apart for easy access to paper path and fold plates
- **Fold Types:** Z, C*, Half and custom folds
- **LED Control Panel:** Notifies operator when the power is on, a cover is open, the paper runs out, or if a fault occurs
- **Fault Detector:** Detects double feeding and any faults
- **Dedicated Use:** Designed for in-line use only
- **Six-Digit Resettable Counter**



FD 2002IL System shown with IL Pressure Sealer and Alignment Base, laser printer (not included), and optional locking cabinets and 18" conveyor

Secure Processing of One-Piece Mailers

The **FD 2002IL System** allows operators to print, fold and seal pressure-sensitive one-piece mailers in one step, reducing processing time while increasing document security. The IL System works in-line with model-specific MICR and non-MICR desktop laser printers. The fully-enclosed paper path is designed to conceal confidential documents, including PIN notices, checks, school grade reports and health care information.

The IL System incorporates the industry-leading FD 2002 AutoSeal® which features a user-friendly LED control panel and pre-marked fold settings for 11" and 14" standard forms. The IL Alignment Base joins the FD 2002IL with the laser printer, and has an easy-pull design which allows the printer to be pulled away from the pressure sealer, providing convenient access to the paper path and fold plates.

The FD 2002IL is ideal for companies processing sensitive documents or those looking for a mid-volume in-line solution for processing pressure seal forms.

Options:

- **P2002IL:** Cost-saving package that includes FD 2002IL System, 18" conveyor and 2 cabinets
- **18" Conveyor w/Photo Eye:** Allows for neat and sequential stacking of processed forms
- **FD 2000-35IL Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output
- **Locking Cabinets:** Fully enclosed for storage (2 cabinets required)

Flexible


The FD 2002IL System handles a variety of documents up to 8.5" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.



User-friendly Control Panel

Pressure Seal Solution

The AutoSeal® FD 2002IL, combined with a laser printer and pressure seal forms, creates a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

Easy to Operate

The AutoSeal® IL System is easy to install. An IL-compatible desktop laser printer (see Specifications, below) is placed on the IL Alignment Base with the FD 2002IL pressure sealer using placement guides to ensure proper alignment. The IL Alignment Base incorporates an easy-pull system which allows the printer to be pulled away from the FD 2002IL to provide convenient access to the paper path and fold plates.

Secure and Strong

The FD 2002IL processes forms securely in a compact and powerful design. The user-friendly control panel features LED indicators and a six-digit resettable counter. The FD 2002IL is built in the USA with proven Formax strength and reliability.



Enclosed paper path provides optimal document security

Specifications:

Printer Compatibility: HP/Troy P2035 (requires FD 2000-45IL Riser)
HP/Troy P2055, P4515, M451 with one optional 500-sheet tray
HP M601, M602, M603, M604, M605, M606, 3015 with optional 500-sheet tray
Lexmark MS711dn with 2100-sheet tray
Xerox Phaser 4510 (requires FD 2000-55IL printer adapter kit)
Additional printers may be compatible. Contact your Account Executive to arrange for testing.

Fold Types: Z & V (all applications), *C (bottom check position only)

Speed: Printer dependent

Paper Size: Up to 8.5" W x 14" L

Usage: Mid-volume

Power: FD Model: 120 Volts AC, 50/60 Hz
FE Model: 220 Volts AC, 50/60 Hz

Dimensions (closed) **: 19" W x 46" L x 23" H

Dimensions w/18" Conveyor (closed): 19" W x 65" L x 23" H

Tabletop Area Required: 20" W x 43" L

Tabletop Area Required w/18" Conveyor: 20" W x 69" L

Dimensions w/Cabinets & 18" Conveyor: 20" W x 74" L x 48" H

Made in the USA



Pre-marked adjustable fold plates



Standard Catch Tray

** Dimensions include IL Pressure Sealer and IL Alignment Base (both included) and laser printer (not included in system)