

Triumph®

by IDEAL

→ 4810 EP SEMI-AUTOMATIC PROGRAMMABLE CUTTER

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt control (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | programmable "EP" back gauge control module with LED display stores 9 programs (up to 9 steps each) and frequently used measurements | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | electric blade and back gauge drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | spindle clamping system applies even pressure along entire cutting width | dual side guides on front and rear tables | spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H): 38 1/4 x 29 3/4 x 53 1/2 inches, Shipping weight: 524 lbs.



"EP" CONTROL MODULE



The "EP" back gauge control module features a digital display and keypad for programming.

FRONT SAFETY GUARD



The transparent front safety guard is electronically secured.

→ TRIUMPH 4810 EP

Cutting width	18 7/8"
Cutting height	3"
Narrow cut	1 3/8"
Cutting length behind blade	17 11/16"
Table length in front of blade	13 3/4"
Motor	1.5 hp
Power supply	115 V, 60 Hz

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com