

Triumph[®]

by IDEAL

↳ 5550 EP PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | programmable "EP" back gauge control module with LED display stores 9 programs (up to 9 steps each) and frequently used measurements | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | hydraulic blade and adjustable hydraulic clamp drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | clamp pressure is fully adjustable between 1,900 and 3,800 psi | false clamp and foot pedal for pre-clamping | electric, spindle-guided back gauge drive | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | mounted on casters | durable stainless steel work surface, front and rear | all-metal construction | optional side tables extend working surface

Dimensions (D x W x H): 55 x 37 7/8 x 54 inches (59 7/8" W with side tables), Shipping weight: 970 lbs. (1,007 with side tables).




"EP" CONTROL MODULE



The "EP" back gauge control module stores 9 programs and frequently used measurements.

SIDE TABLES



Optional side tables extend the working surface.

↳ TRIUMPH 5550 EP

Cutting width	21 5/8"
Cutting height	3 5/8"
Narrow cut	1 1/4"*
Cutting length behind blade	22 7/8"
Table length in front of blade	18"**
Motor	2 hp
Power supply	115 V, 60 Hz ¹

* 2 1/8" with false clamp

** 14 1/2" with guard down

¹ 20 amp dedicated line required

Dealer: **LSS Digital**
4501 S. Pinemont #100
Houston, Texas 77041

LSS Digital
1331 U.S. Highway 80 #12
Mesquite, Texas 75150

877.460.1212 toll free both locations

MBM
 CORPORATION

3134 Industry Drive
 North Charleston, South Carolina 29418
 800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
 CORPORATION

1675 Sismet Road, unit 4
 Mississauga, Ontario L4W 4K8
 800-387-2528, fax: 905-840-1114
www.ideal-mbm.com