

Triumph[®]

by IDEAL

➔ 5551-06 EP PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: front safety light beams; safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | programmable "EP" back gauge control module with LED display stores 9 programs (up to 9 steps each) and frequently used measurements | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | hydraulic blade and adjustable hydraulic clamp drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | clamp pressure is fully adjustable between 1,900 and 3,800 psi | false clamp and foot pedal for pre-clamping | electric, spindle-guided back gauge drive | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | mounted on casters | durable stainless steel work surface, front and rear | all-metal construction | optional side tables (shown) extend working surface

Dimensions (D x W x H): 55 x 42 x 54 inches (64 W with side tables), Shipping weight: 970 lbs. (1,007 with side tables).



5551-06 EP shown with optional side tables.



SAFETY LIGHT BEAMS



Safety light beams protect the operator and allow back gauge to automatically advance to the next cut.

"EP" CONTROL MODULE



The "EP" back gauge control module features a digital display and keypad for programming.

➔ TRIUMPH 5551-06 EP

Cutting width	21 3/8"
Cutting height	3 3/8"
Narrow cut	1 1/2"*
Cutting length behind blade	22 7/8"
Table length in front of blade	18"
Motor	2 hp
Power supply	115 V, 60 Hz**

* 2 3/8" with false clamp

** 20 amp dedicated line required

Dealer: **LSS Digital**
4501 S. Pinemont #100
Houston, Texas 77041

LSS Digital
1331 U.S. Highway 80 #12
Mesquite, Texas 75150

877.460.1212 toll free both locations

MBM
 CORPORATION

3134 Industry Drive
 North Charleston, South Carolina 29418
 800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
 CORPORATION

1675 Sismet Road, unit 4
 Mississauga, Ontario L4W 4K8
 800-387-2528, fax: 905-840-1114
www.ideal-mbm.com